

## HT1800UV-GEN6

Premium Roll-to-Roll Printing



- Supports Full-color and White UV Printing Solutions
   Precise printing with seamless transitions.
- Industrial-grade High-precision Equipment Compact structure with superior stability.
- Simultaneous Printing of Front and Back Multi-color modes freely adjustable.

- Ensures Media Stability
   Maintains smooth, wrinkle-free printing for long-term operations.
- Accurate and Efficient Operation
   Exceptional cost performance with enhanced productivity.
- Global After-sales Service Coverage
   24/7 professional after-sales support for customer peace of mind.





## **Technical Parameters:**

Model		HT1800UV-GEN6
Printing Inform	mation	
Printhead		GEN6
Number of Printheads		2 - 8 pcs (3-row)
Resolution		605*1800 DPI
Productivity	Draft Mode	65 m²/h
	Production Mode	56 m²/h
	Quality Mode	41 m²/h
Printing Modes		Unidirectional & Bidirectional
Media & Ink		
Max. Print Width		1800 mm
Max. Media Thickness		50 mm
Media		Flexible flat materials
Ink Type		UV (VOC free)
Ink Colors		CMYK, Lc, Lm, W
Software & Fe	atures	
Curing		Water-cooled UV_LED Lamp
Transfer		High-speed PCIE
RIP		Caldera
Input		PDF, JPEG, TIFF, EPS, Al
Dimensions &	Weight	
Machine Dimensions		4515*960*1335 mm (L*W*H)
Net Weight		1200 KG
Gross Weight		1500 KG
Power & Envir	onment	
Power Consumption		4 kW (19A)
Power Supply		220VAC 50Hz 3P/N/PE
Environmental Requirements		Independent, clean, low-dust, low-light workspace with good ventilation
		Operating Temperature: 18°C ~ 30°C (64°F ~ 86°F)

## Industrial Digital Inkjet Comprehensive Solution Provider



Independent printhead-drive technology



Self-developed control system



Relative Humidity: 30% ~ 70% (non-condensing)

Self-developed MES system



Independent ink industrial chain



Remote service maintenance system and local services