

UV Hybrid Printer - Ricoh Series



Optional Models:

- **HT1600UV** Easily competent for small and medium orders
- **HT2500UV** Cost-effective choice for coils and sheets in medium size
- **HT3200UV** Smart choice for large-format high-speed hybrid printing

Outstanding Performance:

- 

Automatic Negative Pressure System
- 

Automatic Height Measurement System
- 

Adjustable UV Curing Power
- 

Sensitive Collision Avoidance Device for the Carriage
- 

Automatic Alignment System (HT3200)
- 

Adjustable Suction Area
- 

Optional Anti-Static Bar
- 

Positioning Rod
- 

Integrated Software Functions
- 

High-Quality Imported Components


HANGLORY GROUP

HANGLORY GROUP


HANGLORY GROUP

UV Hybrid Printer - Ricoh Series						
Model		HT1600UV	HT2500UV	HT3200UV		
Printing Information						
Printhead		GEN6				
Number of Printhead		2-8 Pcs (2-Row)	4-8 Pcs (2-Row)	4-8 Pcs (2-Row)	4-8 Pcs (3-Row)	2-16 Pcs (4-Row)
Resolution		1200*1200 DPI		1210*1200 DPI		
Production Mode	Draft	52 m ² /h	65 m ² /h	74 m ² /h	93 m ² /h	108 m ² /h
	Production	36 m ² /h	44 m ² /h	55 m ² /h	80 m ² /h	94 m ² /h
	Quality	28m ² /h	30 m ² /h	40 m ² /h	55 m ² /h	68 m ² /h
Print Mode		Unidirectional & Bidirectional				
Media Ink						
Max. Print Width		1.6 m	2.5 m	3.2 m		
Max. Media Thickness		50 mm				
Media Type		Sheet Material: Signage, acrylic, metal sheets, PVC sheets, KT boards and more. Roll Material: Light sheets, soft films, car stickers, printed fabrics, knife-coated fabrics and more.				
Ink		Environmentally friendly UV / LED curable ink (VOC free)				
Ink Color		CMYK, Lc, Lm, W (Varnish optional)	CMYK, Lc, Lm, W, V			
Software Functions						
UV Curing		LED				
Interface		High Speed PCIE				
RIP Support		Caldera				
Image Format		PDF, JPEG, TIFF, EPS, AI,etc.				
Dimension Weight						
Machine Size(L*W*H)		4.15*1.19*1.33 m	5.49*1.15*1.38 m		6.19*1.59*1.56 m	
Machine Net Weight		760 KG	1280 KG		2260 KG	
Machine Gross Weight		1170 KG	1875 KG		3130 KG	
Power Supply Environment						
Power Consumption		5.3 kW (27A)	8.3 kW (20A)		9.0 kW (20A)	
Power Supply		230VAC 50Hz L/N/PE	400VAC 50Hz 3P/N/PE			
Environment		Separate workroom in cleaning and ventilated condition, avoid direct sunlight. Temperature:18-30°C(64-86 °F) Constant Humidity:30-70% (non-condensing)				

Industrial Digital Printing Solution Provider

- 

Independent printhead-drive technology
- 

Self-developed control system
- 

Self-developed MES system
- 

Independent ink industrial chain
- 

Remote service maintenance system and local services



Shenzhen HandTop Tech Co.,Ltd
Add: No.39 Qingfeng Road, Baolong Street, Longgang District, Shenzhen (2-3/F, Building C, Jingmida Digital Culture Industry Park - HanGlory Group)
Tel: +86 0755-23080896 / 23062862 **E-mail:** info@hanglorygroup.com
Fax: +86 0755-23217841 **Web:** www.hanglorygroup.com/en

© The above information is for reference only. Shenzhen HandTop Tech Co.,Ltd. reserves the right of final interpretation. Descriptions, illustrations and specifications here of are subject to change without prior notice. Final details shall be subject to contract signed.

V2.0/2024

HANGLORY GROUP

HANGLORY GROUP

HANGLORY GROUP